

TECHNICAL SPECIFICATIONS



MATRIX SPARSH VP510E – Premium IP Phone for Business

SPARSH VP510E is one of the Premium IP Phones with preloaded all VOIP Phone Handset features to serve the purpose of a Business Office Phone.

SPARSH VP510E sets the benchmark for quality performance with elegant design and crystal clear voice. SPARSH VP510E features an LCD Graphical Display, Context-Sensitive Keys, Direct Station Selection (DSS) keys, 32 Keys Expansion Module, Headset Connectivity, High-Quality Full Duplex Speaker Phone, and High Definition Audio Quality.

SPARSH VP510E acts as the face of your communication system by delivering advanced features such as Multiple Call Line Appearance, Context Sensitive Soft Keys, Busy Lamp Field, Voice Mail, Speed Dial, and Corporate Directory.

Parameters	Features
Audio Features	 Full-duplex Hands-free Speakerphone with AEC Codecs: G.711(A/μ), G.722, G.723, G.729, iLBC AEC, AJB, AGC
Phone Features	Call HoldMute

	Do Not Disturb
	Speed Dial
	Hotline
	Redial
	Call Back
	Auto Answer
	Call Forward
	Call Waiting
	Call Transfer
	Room Monitoring
	Conference
	Directory
	Call Logs
	Paging
	Dial-by-Name
	Message Wait Lamp
	Ringer Lamp
	Voice Mail
Call Management	Call Pickup - Group and Selective
	Paging
	240*64 Pixels Graphical LCD with Backlit
Display	LED for Incoming/Ongoing Call, Mute and Hold
	Intuitive User Interface with Icons
	Multiple Languages
	Caller ID with Name and Number
	• SIP v2 (RFC3261)
	IP Assignment: Static/DHCP/PPPoE
	• QoS: 802.1p/Q Tagging (VLAN),
	Layer 3 ToS, DSCP
Networking and	SRTP for Voice
Security	Transport Layer Security (TLS)
,	AES Encryption for Configuration File
	Digest Authentication using MD5
	IEEE802.1X
	- ILLLOUZ.IA
	2 /Cigobit Ports DC and LAN)
Ethernet Ports	2 (Gigabit Ports - PC and LAN)

Physical Features	 49 keys including 4 Context Sensitive Keys 1 x RJ9 Handset Port 1 x RJ9 Headset Port Dimension (L x B x H): 247 X 183 X 43 mm
Power Supply	 Power Adapter: 5VDC/600mA Power over Ethernet (IEEE 802.3af) Power Consumption: 5W (Typical) Connector: DC Power Jack
Mechanical	 Weight: 0.805 Kg Installation: Wall Mount, Table-top Color: Black
Environmental	 Operating Temperature Range = 0 to 45°C Storage Temperature = 0 to 55°C Operating and Storage Humidity = 5 to 95%, RH, Non-Condensing
Certifications	CE, FCC-15, RoHS

Note: Specifications are subject to change without prior notice

ABOUT MATRIX

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern organizations. Matrix offers a comprehensive range of solutions for IP Video Surveillance, Access Control, Time-Attendance, and Telecom applications. The solutions are designed to meet the communication and security requirements of large enterprises having offices in multiple locations, SMEs, and SMBs.

As an innovative, technology-driven, and customer-focused organization, Matrix is committed to keeping pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched over 60 cutting-edge products and solutions.

IP Video Surveillance includes solutions like Video Management Systems, Network Video Recorders, and IP Cameras. Likewise, solutions in Access Control and Time-Attendance include Visitor Management Solutions, Elevator Access Control, Panels, Door Controllers, and Readers.

We offer Telecom Solutions such as Unified Communications, IP-PBX, Universal Media Gateways, VoIP and GSM Gateways, and Communication Endpoints. All these solutions are feature-rich, reliable, and conform to international standards.



MATRIX COMSEC Head Office 394-GIDC, Makarpura, Vadodara-390 010, India. Ph: +91 265 6137222

 $\hbox{E-mail: Inquiry@MatrixComSec.com}\\$

Factory
19-GIDC, Waghodia, Dist. Vadodara-391 760, India.
www.MatrixComsec.com