



TECHNICAL SPECIFICATIONS



SIMADO GFX11E – GSM (2G) Fixed Cellular Terminal for Voice Applications

SIMADO GFX11E is a specialized GSM[#] (2G) FCT that enables critical communication during emergency situations such as elevator breakdowns and power cuts. GFX11E establishes a communication link with the help center to allow a user in trouble to get immediate help. SIMADO GFX11E can be used in various application areas such as elevators, ATM Centers, arcades, hospitals, shopping malls, and senior citizens’ homes.

PRODUCT VARIANTS	
SIMADO GFX11E	GSM (2G) FCT for Emergency Applications

Parameters	Specifications
Mobile Port	
GSM (2G) SIM Card	1
Frequency Bands	Quad-band: 850/ 900/ 1800/ 1900MHz

RF Transmission Power	Class 4 (2W @850/ 900MHz) Class 1 (1W @1800/ 1900MHz)
RF Sensitivity	GSM850: -109dBm GSM900: -109dBm DCS1800: -109dBm PCS1900: -109dBm
SIM Interface	1.8, 3V SIM Interface
Compliance	ETSI GSM Phase2/2+

FXS Port	
Connector	RJ11
Pulse Dialing	10 PPS +/- 10%, Make/Break = 33:67ms
DTMF Dialing and Reception	ITU-T Q.23 and Q.24
Off Hook AC Impedance	600Ω
Loop Feed	35mA (Max.)
Loop Limit	270Ω (Excluding telephone)
On-Hook Voltage (Tip-Ring)	-48V nominal
Return Loss	>18dB
Longitudinal Balance	>40dB
Ringing Voltage	Trapezoidal: 55Vrms@25Hz
Caller ID Presentation	DTMF and FSK ITU-T V.23 and FSK Bellcore 202A
Answering and Disconnect Signaling	Polarity Reversal for Call Connect/Disconnect Signaling
Protection	Solid-state over voltage Secondary Protection

Battery	
Internal Battery	NI-MH AAA 7.2V/800mA

Power Supply	
Input	12VDC@1.25A External Power Adapter (100-240 VAC, 47-63Hz) supplied by Matrix

Power Consumption	5W (Typical)
Connector	Casio DC Power Jack
Battery Back-up	4 hours (idle mode) 2 hours (talking mode)
LED Indications	Battery (BAT), Power Supply (PWR), Network (NW), SIM (RDY), FXS Port (FXS)

Mechanical	
Dimension (mm)	Width 133.5 x Height 198 x Depth 44.6 (5.26"x 7.80"x 1.76")
Mounting Options	Wall Mount and Tabletop
Unit Weight	0.4 kg. Approx.
Shipping Weight	0.9 kg. Approx.

Antenna	
Antenna Type	Monopole Omni Directional Swivel Antenna
Antenna Gain	1/3 dBi
Antenna Connector	SMA (Male), 50Ω

Environmental Conditions	
Storage Temperature	-40°C to +85°C (-40°F to +185°F)
Storage Humidity	0-95% RH, non-condensing
Operating Temperature	0°C to +45°C (34°F to +113°F)
Operating Humidity	5-95% RH, non-condensing

#: *For compatibility and use of Matrix GSM products in Russia and Iran province connect with Matrix sales or technical support team*

Note: *Specifications are subject to change without prior notice*

ABOUT MATRIX

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern organizations. Matrix offers a comprehensive range of solutions for IP Video Surveillance, Access Control, Time-Attendance, and Telecom applications. The solutions are designed to meet the communication and security requirements of large enterprises having offices in multiple locations, SMEs, and SMBs.

As an innovative, technology-driven, and customer-focused organization, Matrix is committed to keeping pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched over 60 cutting-edge products and solutions.

IP Video Surveillance includes solutions like Video Management Systems, Network Video Recorders, and IP Cameras. Likewise, solutions in Access Control and Time-Attendance include Visitor Management Solutions, Elevator Access Control, Panels, Door Controllers, and Readers.

We offer Telecom Solutions such as Unified Communications, IP-PBX, Universal Media Gateways, VoIP and GSM Gateways, and Communication Endpoints. All these solutions are feature-rich, reliable, and conform to international standards.



MATRIX COMSEC

Head Office

394-GIDC, Makarpura,
Vadodara-390 010, India.

Ph: +91 265 6137222

E-mail:

Inquiry@MatrixComSec.com

Factory

19-GIDC, Waghodia, Dist.
Vadodara-391 760, India.

www.matrixtelesol.com